

**MICHIGAN UNIFORM ENERGY CODE COMPLIANCE FORM**

Part 10 of the State Construction Code  
R 408.31061 ET.SEQ

JOB \_\_\_\_\_

ADDRESS \_\_\_\_\_ MUNICIPALITY \_\_\_\_\_

BUILDER \_\_\_\_\_ SUBMITTED BY \_\_\_\_\_

BUSINESS PHONE \_\_\_\_\_

Check Method of Compliance: Prescriptive \_\_\_\_\_ Systems Approach \_\_\_\_\_

NOTE: Systems Approach method requires an energy analysis comparison report (ARF 1086.3)

1. Gross area of exterior walls in square feet \_\_\_\_\_

2. Square feet of fenestration openings \_\_\_\_\_

3. Percent of fenestration exterior wall opening \_\_\_\_\_

4. If fenestration openings exceed 20% of gross exterior wall area, indicate the specific trade-off option that will be used for compliance (R408.31083) \_\_\_\_\_  
\_\_\_\_\_

5. Indicate the percentage of exposed basement wall area (sq. ft. of exposed basement wall divided by sq. ft. of gross area of exterior wall). \_\_\_\_\_

6. Indicate the "R" value and type of insulation proposed for use on basement walls to bring exposure down to 7% of the gross area of exterior walls. (R408.31081)

7. Attach documentation for certified or labeled "R" values of all pre-manufactured fenestration products including windows, doors and skylights. (R408.31071)

8. Indicate the proposed insulation "R" value for each component  
Walls \_\_\_\_\_ Slab on grade floors \_\_\_\_\_ Floors over unconditioned space \_\_\_\_\_  
(R408.31074) (408.31078) (R408.31077)

Ceiling/roof \_\_\_\_\_ Crawl space walls \_\_\_\_\_  
(R408.31076) (R408.31079)

9. I agree that at the time of inspection, the insulation installer shall provide a certificate for any blown-in or sprayed insulation that lists the following information:

- a. The initial thickness
- b. The settled thickness
- c. The coverage area
- d. The number of bags used

**SIGNATURE/DATE** \_\_\_\_\_